

GE Healthcare OEC 9800 Plus

A Classic Choice

Tried and true features to manage patient images

- Integrated DICOM 3.0 interface connects to your facility's network
- Optional on-board film and paper printer allows high quality hard copy images without darkroom film processing
- HIPPA SecureView * helps keep patient data private with password protection, blank screen and delete all functions



Standard C 9" (23cm) I.I.



Standard C 12" (31cm) I.I.



Super C 9" (23cm) I.I.



Footswitch & Handswitch
Physician-controlled.



C-arm Controls
Operate the controls from either side of the C-arm.

1k² High Resolution Imaging Chain

High Resolution 9" (23 cm)
Tri-Mode Intensifier
9"- 6"- 4" (23, 15, 10 cm) Modes.

High Power Rotating Anode X-ray Tube

OEC X-ray tube heating technology and small focal spot facilitates longer fluoro on-time.

15 kW Generator

The Powerful generator is separated from the X-ray tube for maximum penetration power without increasing X-ray tube heat or dose. 1,2,4,8 pulse-per-second (pps) imaging modes.



Automatic Imaging Modes

- Fluoro
- High Level Fluoro (HLF)
- Digital Spot
- Roadmap
- Digital Subtraction

When you need a trusted and proven C-arm to help you power through almost any case, choose a classic.

©2012 General Electric Company – All rights reserved.

GE, GE Monogram, OEC and SecureView are trademarks of General Electric Company.

LR-980095-01